

Type	Model	Permeate flow GPD (m ³ /d)	Rejection Rate (%)	Min. Rejection (%)	Testing Conditions			Product Size(mm)	
					Pressure psi (MPa)	Concentration NaCl (ppm)	Recovery (%)	Length	Diameter
ULP Series	ULP1812-50	50(0.19)	99	97	60(0.41)		15	256	46
	ULP1812-75	75(0.28)	98	96					46
	ULP2010-100	100(0.38)	98	96					47.5
	ULP2012-100	100(0.38)	99	97					48
	ULP2012-125	125(0.48)	99	97					48
	ULP2012-150	150(0.55)	98	96					48
	ULP3012-300	300(1.13)	98.5	96.5	250	40	298	73	
	ULP3012-400	400(1.51)	98.5	96.5				73	
	ULP3012-500	500(1.89)	98	96				73	
	ULP3012-600	600(2.27)	98	96				73	
	ULP3012-800	800(3.02)	97	95	100(0.69)	40	333	73	
	ULP3013-400	400(1.51)	98.5	97.5				67.8	
	ULP3013-500	500(1.89)	98	96				67.8	
	ULP3013-600	600(2.27)	98	96				67.8	
ULP3013-800	800(3.02)	97	95					67.8	
ULP Series	ULP3113-800	800(3.02)	98	96	100(0.69)	250	50	333	78
	ULP3113-1000	1000(3.78)	98	96					78
HOR Series	HOR2012-50	50(0.19)	98	96	60(0.41)	250	15	298	48